



Coffeemar XL 46

CTG coffee to go

TECHNOLOGICAL INNOVATION • RELIABILITY • 100% JOFEMAR TECHNOLOGY

Within the Coffeemar range of machines, the XL 46 model has been specially designed to offer the public **large take-away coffee**, or to enable the dispensing of **two types of coffee** in the same machine.



All this is made with the **technology** developed by **Jofemar** for its range of Coffeemar machines, which allows the extraction of all the **quality** of the coffee beans, and includes the top features for a vending machine.

CHARACTERISTICS

- Pressure valve in the brewing unit to maintain constant pressure throughout the dispensing cycle.
- · Motorised water distributor without solenoid valves.
- Aluminium boiler with encapsulated resistance and sensors, without contact with the water (avoiding O-rings and limescale build-up).
- Extractor for cups up to 80 mm diameter and 117 mm high, 350 ml.
- Dispenser for adjustable stirrers between 75 mm and 115 mm long.
- Self-cleaning of the mixing circuit, product outlet and grinding unit: manual or automatic (programmable).
- Against steam sugar addition system, directly to the cup.
- Constant temperature control in the boiler.
- Smooth closing system on the product collection door.
- Easy cleaning and maintenance of removable elements.
- Delivery of lids for the cup, with the possibility of preselection button and price surcharge.
- Double brewing unit, with simultaneous operation, option for two types of coffee, or coffee and tea leaf.

Services	500
Canisters	6 + 2 grano
Selections+preselection	18+2
Whippers	4
Graphic display	92 x 53 mm
Size	1.825 x 755 x 560 mm
Weight	170 kg
Mains water supply	3/4 GAS
Energy supply	230V, 50 Hz*
Maximum power	2.000 watios

*Check for other voltages.



Coffee to go in any location

CONSTRUCTION

- Anti-fingerprint stainless steel finish.
- Cabinet in steel treated against corrosion and vandalproof closing, integrated door in cabin (against crowbars).

CREDIT MANAGEMENT

• MDB payment systems, JF8 coin acceptor, BT11 banknote reader, J-140 card readers, or other compatible systems.

PROGRAMMING

- General on-site programming using the keyboard, Easy-Flash hand terminal, via PC.
- Storage and retrieval of accounts.

OPTIONS

- · Selffeeding water kit (one or two tanks of 25 l each).
- Water filters: water softener or flavour filter.

CAPACITIES

Coffee beans	4.600 g
Powdered milk	1.700 g
Chocolate	1.350 g
Sugar	2.100 g
Freeze dried coffee	700 g
Tea and herbal drinks	1.000 g





OPTIMISED CAPACITY AND VOLUME



ENERGY-SAVING LED LIGHTING



BANKNOTE AND COIN MECHANISM PAYMENT SYSTEMS



MOTORISED WATER DISTRIBUTOR WITHOUT ELECTROVALVES



PRESSURE VALVE IN THE BREWING UNIT



ALUMINIUM BOILER



TOUCH KEYBOARD



SMUDGE-PROOF STAINLESS STEEL



Joremar

