





Automated sale of multi-products

COMBOPLUS R290 V8 COMBOPLUS REFRIGER V8 COMBOPLUS AMBIENT V8

TECHNOLOGICAL INNOVATION • RELIABILITY • 100% JOFEMAR TECHNOLOGY

Vision ComboPlus features EasyFlex, an exclusive flexible extraction system, developed by Jofemar. It stands out for the optimised capacity and volume, and its bespoke cooling unit that controls evenly the temperature inside the vendor, that allows storing and selling soft drinks, snacks and similar products.

FEATURES

• Temperature: with or without cooling unit.

• Capacity up to 8 height-adjustable trays with maximum 7 channels each.

• FIFO (First In First Out) System. Continues renewal with the freshest product. Product dispensing according to loading order.

- Correct sale detection with photocells.
- LED lighting with on/off programming.
- 1.462 x 473.5 mm glass front door.
- Continuous performance self-testing.
- Health timer: Automatic security system to prevent selling out-of-date products. Programmable

expiration date by selection number or channel.

• Flexible setup and programming. Its channel adjustment system allows incorporating new products

at any time without using tools. • Inteligent self-adjusting motor torque for each type of product characteristics, optional manual motor torque adjustment.

- Power mains: 230 V, 50 Hz.
- Assigned power, R290 model: 300 watts.
- Assigned power, Refriger model: 340 watts.
- Assigned power, Ambient model: 30 watts.
- Elevator.
- Color graphic display and capacitive keyboard.
- Selection of products with shopping list or

individual form.

STRUCTURE

• Modular cabinet structure treated against rust and corrosion.

- Vandal-proof security lock with three anchor points.
- High-capacity cash box and optional lock.
- Injected foam insulation system that guarantees
- efficient cooling and lower energy consumption.

PROGRAMMING

• General on site programming and display system for the data accounting, accessible from inside the machine.

• Compatible with the latest telemetry systems for the end-to-end remote machine management.

- DEX port with accounting data output.
- Upgradeable by USB with machines cloning option.



Ctra. Marcilla km 2 31350 PERALTA. Navarra SPAIN Tel. +34 948 75 12 12 Fax +34 948 75 04 20 **www.jofemar.com**



CREDIT MANAGEMENT

- MDB or Executive protocol.
- Innovative Jofemar coin mechanism with the most reliable fraud-prevention systems.
- Card and banknote readers can be fitted.

OPTIONS

- It can incorporate cooling unit.
- Jofemar banknote reader.
- Jofemar card/key reader or any MDB card reader.
- Vandal-proof coin entry.
- J-LINK telemetry interface with communication with
- the vending management platform J-SUITE.
- Online operation with real-time control of users an sales.

• Management of up to three satellite vending machines for higher capacity and number of selections.

• External microwave ovens managed by the control unit machine. Self-activated when a product has been dispensed from the vender. Single programmed heating time per selection.



TemperatureWith/Without cooling unitMaximum capacityUp to 8 trays of max. 7 channelsElevatorYesSize (mm)1.835 x 800 x 1.025Weight341 kgEnergy supply230 V, 50 Hz*Cooling unitOptional		COMBOPLUS R290 V8
ElevatorYesSize (mm)1.835 x 800 x 1.025Weight341 kgEnergy supply230 V, 50 Hz*	Temperature	With/Without cooling unit
Size (mm) 1.835 x 800 x 1.025 Weight 341 kg Energy supply 230 V, 50 Hz*	Maximum capacity	Up to 8 trays of max. 7 channels
Weight 341 kg Energy supply 230 V, 50 Hz*	Elevator	Yes
Energy supply 230 V, 50 Hz*	Size (mm)	1.835 x 800 x 1.025
	Weight	341 kg
Cooling unit Optional	Energy supply	230 V, 50 Hz*
	Cooling unit	Optional

*Check for other voltages.





VANDAL-PROOF LOCK



BANKNOTE AND COIN MECHANISM

PAYMENT SYSTEMS



EASYFLEX DELIVERY SYSTEM



HEALTH TIMER: EXPIRATION PROGRAMMING BY TEMPERATURE



PRODUCT DELIVERY DETECTION PHOTOCELLS





EXPIRATION PROGRAMMING